38th St. 3800 N OFFICE OF THE MARION COUNTY SURVEYOR SECTION RECORD CORNER SECTION ____19_TOWNSHIP ___ ш 16 RANGE 4 DATE: 10-23-06 PARTY CHIEF: Wilcoxen CREW: TYPE OF MARKER: Cut 'x' N curb of median METHOD OF ESTABLISHMENT: ___County: 1-16-04 IN. S.P.C. E ZONE NAD '83 ' NAME: 16041901 508234.3393 (m) N: E: 59449.3537(m) 1. (PWP) 38th Street 3800 N Watson

Original post set 1820 by Hendricks with witness: 16" sugar S 22 E 6 links; 15" dogwood N 26 W 7 links per Marion County Atlas. Survey by Fatout 4-1-1872 called no stone nor witness per Center Township Legal Survey Book pg. 4. in establishing this corner we used the Marion Highland subdivision and legal survey distances and curb splits per Plat Book H pg. 26 & 47. 10-28-97 a copperweld was set by Wilcoxen. Re-tied 1-16-04 by Wilcoxen. Re-tied 10-23-06 by Wilcoxen.

<u> </u>	1604190	11
REF.	DISTANCE	DE'SCRIPTION
1.	69.97	Mag nail w/bw NW PwP no# 8" up
2.	100.53'	Due S to cut 'x' in concrete road NF cor. 24-16-3
3.	9.63'	NW corner of light stone column
4.	84.39'	Mag nail W PwP#612-407 A 6"up
*		
	- 11	